



Shielding clamp with spring

PRODUCT DESCRIPTION

The Shielding clamp with spring is used for the connection of cable shields with the ground level.

The clamp is available for direct mounting, assembly on busbar or 35 mm DIN rails.

ADVANTAGES

- // through spring pressure steady contact to the cable shield
- // wide clamping range

TECHNICAL DATA

Material: galvanised steel

ACCESSORIES

- // Clip foot for 35 mm DIN rail, M4
- // Busbar 10 x 3 x 1.000 mm

SHIELDING CLAMP WITH SPRING AND CLIP FOOT

| ITEM DESCRIPTION | ORDER NO. | SHIELD DIAMETER | PU |
|------------------|-----------|-----------------|----|
| SF-SK 3-8 | 1042-001C | 3-8 mm | 10 |
| SF-SK 4-13,5 | 1042-002C | 4-13,5 mm | 10 |
| SF-SK 10-20 | 1042-003C | 10-20 mm | 10 |
| SF-SK 15-32 | 1042-004C | 15-32 mm | 10 |
| Clip foot M4 | 1030-020D | | 25 |

SHIELDING CLAMP FOR DIRECT MOUNTING

| ITEM DESCRIPTION | ORDER NO. | SHIELD DIAMETER | PU |
|------------------|-----------|-----------------|----|
| SK 3-8 | 1042-011C | 3-8 mm | 10 |
| SK 4-13,5 | 1042-012C | 4-13,5 mm | 10 |
| SK 10-20 | 1042-013C | 10-20 mm | 10 |
| SK 15-32 | 1042-014C | 15-32 mm | 10 |

SHIELDING CLAMP FOR BUSBAR

| ITEM DESCRIPTION | ORDER NO. | SHIELD DIAMETER | PU |
|------------------|-----------|-----------------|----|
| SKO 3-8 | 1042-021C | 3-8 mm | 10 |
| SKO 4-13,5 | 1042-022C | 4-13,5 mm | 10 |
| SKO 10-20 | 1042-023C | 10-20 mm | 10 |
| SKO 15-32 | 1042-024C | 15-32 mm | 10 |
| Busbar 10 x 3 | 1046-001B | length 1.000 mm | 5 |